



Pacific Polymers

A Division of **ITW**

12271 Monarch Street
Garden Grove, CA 92841
(800) 888-8340

MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT ELASTO-POXY PRIMER (D & G) (B-Component) MSDS DATE: January 8, 2010

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: ELASTO-POXY PRIMER (D & G) B-COMPONENT
PRODUCT CODES: EPP-DG-B

MANUFACTURER: PACIFIC POLYMERS
DIVISION: A DIVISION OF ITW
ADDRESS: 12271 MONARCH STREET, GARDEN GROVE, CA 92841
INFORMATION PHONE: 714-898-0025
FAX NUMBER: 714-898-5687

EMERGENCY PHONE: 1-800-424-9300 CHEMTREC

PRODUCT USE: TWO COMPONENT, DAMP AND GREEN, SOLVENT BASED EPOXY PRIMER FOR CONCRETE
PREPARED BY: PACIFIC POLYMERS

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

<u>INGREDIENT</u>	<u>CAS NO</u>	<u>Wt%</u>
Polyamine Mixture	Mixture	25 - 35
Xylene	1330-20-7	65 - 75%
Ethyl Benzene	100-41-4	< 15%

SECTION 2 NOTES: All ingredients are TSCA listed. Xylene contains ethylbenzene (cas# 100-41-4) less than 15% by weight in the formulated product)

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Caution! Flammable Liquid and vapor. May form explosive mixtures with air. Harmful in contact with skin. Inhalation of vapor may cause headaches, dizziness, drowsiness and nausea. May cause respiratory tract, eye and skin irritation. May cause allergic skin reaction.

ROUTES OF ENTRY: Skin, Inhalation, eye, ingestion

Potential Acute Health Effects

Eyes: Irritating to eyes

Skin: Irritating to skin. May cause skin sensitization on skin contact.

Ingestion: Not expected to be a relevant route of exposure. However product may be moderately harmful if swallowed. May cause central nervous system depression.

Inhalation: Product may cause irritation to the nose, throat, and respiratory tract. May cause central nervous system depression.

Potential Chronic Health Effects

Chronic Effect: The product contains material that can cause target organ damage. The product contains materials that may cause target organs : blood, kidney, liver, central nervous system.

Over-Exposure signs/symptoms

Eyes: pain or irritation, watering, redness

Skin: irritation, redness, defatting, scaly dermatitis on prolonged and repeated contact.

Ingestion: nausea or vomiting, dizziness/vertigo, drowsiness/fatigue, headache, unconsciousness

Inhalation: respiratory tract irritation, coughing, nausea or vomiting, dizziness/vertigo, drowsiness/fatigue, headache, unconsciousness

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Pre-existing skin disorders and disorders involving any other target organs mentioned in the MSDS as being at risk may be aggravated by over-exposure to this product.

SECTION 4: FIRST AID MEASURES



Pacific Polymers

A Division of **ITW**

12271 Monarch Street
Garden Grove, CA 92841
(800) 888-8340

MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT ELASTO-POXY PRIMER (D & G) (B-Component) MSDS DATE: January 8, 2010

EYES: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids for proper irrigation of eyes. Check for and remove any contact lenses. Get medical attention promptly.

SKIN: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly before reuse. Dispose contaminated gloves. Clean shoes thoroughly before reuse. Consult physician if irritation persists.

INHALATION: Get medical attention. Move person to fresh air. If breathing is difficult, provide oxygen. Provide artificial respiration if not breathing. If unconscious, get medical help immediately. Maintain an open airway. Loosening tight clothing such as collar, tie, belt or waistband may help.

INGESTION: Get medical attention. Wash out mouth with water. Remove dentures, if any. Keep person warm and at rest and move to fresh air if possible. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, keep head below hips to prevent aspiration of liquid into the lungs. Never give anything by mouth to an unconscious person.

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR, UPPER: 7.0 (Xylene)
(% BY VOLUME) LOWER: 1.0 (Xylene)

FLASH POINT: 80F METHOD USED: Pensky Marten Closed Cup Tester

AUTOIGNITION TEMPERATURE: 810F (Xylene)

HMIS HAZARD CLASSIFICATION

HEALTH: 3 FLAMMABILITY: 3 REACTIVITY: 0
PROTECTION: respirator, gloves, chemical safety goggles/glasses, coverall/apron

EXTINGUISHING MEDIA: Use dry chemical, carbon dioxide, water spray (fog) or foam.

SPECIAL FIRE FIGHTING PROCEDURES: This component of the product is flammable. Clear fire area of unprotected personnel. Do not enter confined, fire space without full bunker gear (helmet with face shield, coats, gloves, and rubber boots. Wear NIOSH approved self-contained breathing apparatus. Cool fire exposed containers with water.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure.

HAZARDOUS DECOMPOSITION PRODUCTS: Decomposition products may include oxides of carbon, and nitrogen.

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: In case of container leak, place in a large container or replace the container. In case of large spill, immediately dike the area, turn off ignition sources, and collect the spill in waste container. Use of inert absorbent may be useful to absorb the product. Do not smoke. Do not weld around the product during usage or while stored. Do not allow spill to enter drains and sewer system.

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE: Wear protective clothing and equipment. Store material in a dry cool area. Do not store above 90F. Use proper tools to open the containers. Grounding of metal containers is always a good practice. Do not smoke while and around the product during usage and application. Avoid welding.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

VENTILATION : Provide local and general ventilation to avoid vapor concentration above TLV limits. Use of explosion proof ventilation may require in some applications such as confined area.

RESPIRATORY PROTECTION: Wear properly fitted organic vapor cartridge respirator or air supplied respirator when/if required by rule and regulation.



Pacific Polymers

A Division of **ITW**

12271 Monarch Street
Garden Grove, CA 92841
(800) 888-8340

MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT ELASTO-POXY PRIMER (D & G) (B-Component) MSDS DATE: January 8, 2010

EYE PROTECTION: Safety eyewear complying with approved standard should be used to avoid exposure to liquid splashes, mists, gases or dusts.

SKIN PROTECTION: Use of coveralls and aprons should help avoid skin contact. Wear chemical resistant impervious gloves to avoid hand contact.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: A monitoring equipment may require to monitor the exposure limits, personal, workplace atmosphere etc. and to determine the necessity to use respiratory protective equipment as well as to determine the effectiveness of the ventilation or other control measures.

WORK HYGIENIC PRACTICES: Wash hands, forearms and face thoroughly after handling the product, before eating, smoking and using the lavatory as well as at the end of the working period. Do not smoke around the applied area. Wash contaminated clothing before reuse. Ensure that eyewash stations and safety showers are close to the workstation location.

EXPOSURE GUIDELINES:

<u>Ingredient</u>	<u>Cas#</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL STEL</u>
Xylene	1330-20-7	100 ppm	150 ppm
Ethylbenzene	100-41-4	100 ppm	125 ppm

<u>Ingredient</u>	<u>Cas #</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH TLV STEL</u>
Xylene	1330-20-7	100 ppm	150 ppm
Ethylbenzene	100-41-4	100 ppm	125 ppm

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: clear to straw yellow low viscosity liquid mixture

ODOR: mild to moderate odor

PHYSICAL STATE: liquid

BOILING POINT: not available

MELTING POINT: not applicable

FREEZING POINT: no data

VAPOR PRESSURE (mmHg): 7 mm Hg (@25C) (Xylene)

VAPOR DENSITY (AIR = 1): greater than air

Weight per Gallon: 7.5 – 7.8 pound per gallon

EVAPORATION RATE: greater than air

BASIS (air =1)

SOLUBILITY IN WATER: slight

VOLATILE ORGANIC COMPOUNDS (VOC): 640 grams per liter

VISCOSITY: 500 cps maximum

SECTION 9 NOTES: vapor density on Xylene is 3.7.

SECTION 10: STABILITY AND REACTIVITY

STABILITY: stable

CONDITIONS TO AVOID (STABILITY): avoid exposure to high temperature. Avoid heat, sparks, and flame.

INCOMPATIBILITY (MATERIAL TO AVOID): Avoid contact with strong oxidizing agents, strong acids and bases.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: carbon monoxide, aldehydes and acids and other organic compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: not expected. Avoid high temperature storage. High temperature may cause pressure buildup in the container that could result to rupture of the container.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

<u>Ingredient</u>	<u>Acute Oral LD50</u>	<u>Acute Dermal LD50</u>	<u>Acute Inhalation LC50</u>
-------------------	------------------------	--------------------------	------------------------------



Pacific Polymers

A Division of **ITW**

12271 Monarch Street
Garden Grove, CA 92841
(800) 888-8340

MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT ELASTO-POXY PRIMER (D & G) (B-Component) MSDS DATE: January 8, 2010
Xylene 4300 mg/kg (rat) >1700 mg/kg (rabbit) 5000 ppm/4h (rat)
Ethylbenzene 3500 mg/kg (rat) - 55mg/l/2h (rat), 35.5 mg/l/2h (mouse)

Other Information:

Carcinogenicity Classification:

<u>Ingredient</u>	<u>ACGIH</u>	<u>IARC</u>	<u>NTP</u>	<u>OSHA</u>
Xylene	not classified	not classified	not listed	not regulated
Ethylbenzene	yes (animals) Unknown (humans)	yes, group 2B	not listed	not regulated

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION:

Environmental Effects: no known effects or critical hazards.

Aquatic Ecotoxicity

Xylene – Fresh water, acute LC50 13.4 mg/l/96hr (fathead minnow)
Fresh water, acute LC50 780 mg/l/96 hr (species 262)
Fresh Water, acute LC50 15.7 mg/l/96hr (Bluegill)
Fresh Water, acute LC50 34.73 mg/l/96hr (Guppy)
Ethylbenzene - Fresh water, acute LC50 9.09 mg/l/96hr (fathead minnow)
Fresh water, acute LC50 4.2 mg/l/96hr (rainbow trout)
Fresh Water, acute LC50 32 mg/l/96hr (Bluegill)
Fresh Water, acute LC50 9.6 mg/l/96hr (Guppy)
Salt Water – Acute LC50 280 mg/l/96hr (sheephead minnow)

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: The generation of waste should be avoided or minimized whenever possible. Dispose of the product via a licensed waste disposal contractor. Avoid any material to enter soil, waterways, drains and sewer.

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION

PROPER SHIPPING NAME: Resin Solution (Xylene)
HAZARD CLASS: Class 3
ID NUMBER: UN1866
PACKING GROUP: III
LABEL STATEMENT: Flammable Liquid Mixture

WATER TRANSPORTATION

PROPER SHIPPING NAME: Resin Solution (Xylene)
HAZARD CLASS: Class 3
ID NUMBER: UN1866
PACKING GROUP: III
LABEL STATEMENTS: Flammable Liquid Mixture

AIR TRANSPORTATION

PROPER SHIPPING NAME: Resin Solution (Xylene)
HAZARD CLASS: Class 3
ID NUMBER: UN1866
PACKING GROUP: III
LABEL STATEMENTS: Flammable Liquid Mixture



Pacific Polymers

A Division of **ITW**

12271 Monarch Street
Garden Grove, CA 92841
(800) 888-8340

MATERIAL SAFETY DATA SHEET

NAME OF PRODUCT ELASTO-POXY PRIMER (D & G) (B-Component) MSDS DATE: January 8, 2010

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT): All ingredients used for the product are in TSCA Inventory.

Sara 311/312 Classification: Immediate (acute) health hazard, delayed health hazard, fire hazard

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT):

Xylene [cas # 1330-20-7]
Ethylbenzene [100-41-4]

SARA 302 Extremely Hazardous Substances : None known

STATE REGULATIONS: Proposition 65: This product contain a chemical known to the State of California to cause cancer and birth defects or other reproductive harm: Ethylbenzene (cas#100-41-4)

INTERNATIONAL REGULATIONS:

WHMIS (Canada): Class B-2: Flammable Liquid

Class D-2A: Material causing other toxic effects

Class D-2B: Material causing other toxic effects.

Canadian Lists: Canadian NPRI: The following ingredients are listed: Xylene, Ethylbenzene

SECTION 16: OTHER INFORMATION

PREPARATION INFORMATION: January 8, 2010

DISCLAIMER:

A MSDS such as this cannot be expected to cover all possible individual situations. The end user of this product has the responsibility to provide a safe workplace. All aspects of an individual operation should be examined to determine if, or where, precautions – in addition to those described herein – are required. Any health and safety information contained herein should be passed on to your customers and/or employees.

The opinions expressed herein are those of qualified experts within Pacific Polymers. We believe that the information contained herein is current as of the date of this Material Safety Data Sheet. Since the use of this information and the use of this product are not within the control of Pacific Polymers final determination of suitability of this product is the sole responsibility of the user. It is the responsibility of the user to comply with all applicable Federal, State and Local laws and regulations.